

PRODUCTO™ FC-115

FLOOR CLEANER









Product Information Flyer

DESCRIPTION

PRODUCTO FC-115 is an economical, industrial strength liquid floor cleaner concentrate. It can also be used for general purpose cleaning.

APPLICATION

PRODUCTO FC-115 is specifically designed for use as maintenance cleaner to remove grease, oil and dirt from machinery, floors, walls and other hard surfaces. It is ideal for use in floor scrubbing machines, steam cleaning, power wash equipment as well as mop/bucket and hand scrubbing operations.

FEATURES & BENEFITS

VERSATILITY:

PRODUCTO FC-115 can be diluted with water in any proportion depending on the severity of the cleaning job.

PRODUCTO FC-115 provides a moderate, controlled level of foam that will not clog floor scrubbers. It does not contain caustics, phosphates, silicates, borates or other inorganic salts.

RECOMMENDED STARTING DILUTIONS

PRODUCTO FC-115 is to be mixed with water for use. Always add concentrate to water. Fluid may be more difficult to mix when water temperature is below 55°F. Add no other materials to the concentrate or mix unless approved by your CIMCOOL® District Manager.

Mechanical Floor Scrubbers: 3% - 5% (1:33 to 1:20)

Mop and Bucket: 5% (1:20)

General Purpose Cleaning: 3% - 100% (1:33 to 1:1)

CONCENTRATION

A refractometer can be used to test concentration. A refractometer is only recommended for use in checking the concentration of a fresh charge.

The Refractometer Factor is 12.5

Multiply the scale reading obtained on your CIMCOOL® Refractometer by this factor to obtain the mix concentration in percent. Calibrate the refractometer so that it reads 0.0 with water before testing the sample mix. Remove gross contaminants from the sample mixes before testing.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Appearance and Odor: Clear/Chemical

Solubility in Water: 100% Miscible Specific Gravity: 1.01

Boiling Point: 212°F VOC Content (by ASTM D2369): 7.1%

pH Concentrate: 9.8 pH Mix 3%: 8.2

HANDLING AND STORAGE

If frozen, product separates. Thaw completely at room temperature and stir thoroughly prior to use. Inside storage is recommended.

SAFETY DATA SHEET

Available at www.cimcool.com

For additional information refer to its OSHA MSDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-513-458-8199.

Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.

