



# Product Information Flyer

## DESCRIPTION

CIMTAP tapping compound is a water soluble paste.

## APPLICATIONS

CIMTAP is a water soluble paste that contains chemical and extreme pressure lubricants. It is recommended for a wide range of tapping operations, from hand tapping to high production automatic jobs on ferrous and non-ferrous metals.

Can be used in three ways

- 1) Applied to tap directly by brushing or dipping
- 2) Diluted from 1:2 (50%) to 1:4 (25%) with water and applied with a squirt can
- 3) For high production on machines with multiple dilutions from 1:20 (5%) to 1:30 (3.3%)

An excellent application for CIMTAP is on parts where the compounds needs to be restricted to the tapped hole to minimize or eliminate subsequent cleaning and washing operations.

Can be used on steels, cast steels, stainless and nickol alloys, aluminum, brass and copper. Not recommended for use on magnesium or magnesium alloys.

## FEATURES & BENEFITS

### MAXIMUM TAP LIFE:

Good lubricity eliminates chip welding, tap burning and resultant tap breakage.

### MAXIMUM PRODUCTION:

Works best at high tapping speeds.

### CLEAN:

Readily soluble in water – Does not leave deposits on the machine – Blind threaded holes can be cleaned with water or an air hose.

## RECOMMENDED STARTING DILUTIONS

### FOR INDUSTRIAL USE ONLY

- For brush on application, use without diluting
- For squirt can application, dilute one part CIMTAP to four parts water
- For multiple operations, add CIMTAP to a CIMCOOL® mix to make a 1:20 (5%) to 1:30 (3.3%) dilution

## TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid

**Solubility in water:** 100% miscible

**Viscosity (SUS) @ 100°F:** Paste

**pH Concentrate:** NA

**Total Chlorine/Chloride, wt%:** 14.4/<50ppm

**Silicones:** None

**Appearance and Odor:** Hazy/Chemical

**Weight, lb/gal, 60°F (15.6 °C):** 8.9

**Flash Point /Sp.Gr./Boiling Point:** SEE MSDS

**pH Mix 10%, Typical Operating:** 9.8

**Total Sulfur, wt%:** 0.5

## HANDLING and STORAGE

Protect from freezing. Inside storage is recommended.

## SAFETY DATA SHEET

Available at [www.cimcool.com](http://www.cimcool.com)

For additional information refer to its OSHA MSDS, website or contact your local CIMCOOL TECHNICAL SPECIALIST OR DISTRICT MANAGER, or you may contact CIMCOOL® Technical Services at 1-513-458-8199.

***Limitation of Liability: Under no circumstances, shall we or any affiliate of ours have any liability whatsoever for loss of use, or for any indirect or consequential damages. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.***